




STRONGDOR
SECURED BY *steel*



Securi*dor*[®]
SECURITY STEEL DOORS



Secure for Sure - It's a Strongdor.



Securidor PAS 24 security doors offer enhanced security performance for internal and external use to application, enable entry and exit. Available as both personnel and emergency exits.

Certified to: PAS 24:2016 Enhanced security performance requirements.

Leaf

Leaf 44mm door leaf thickness, fitted with an integrated astragal for added security. Comprising of 2 x 1.2mm steel sheets, the leaf skins are mechanically interlocked and internally bonded providing greater stability and protection against de-lamination. Insulated core as low as 1.5 U-value.

Rebate frame

Manufactured from lightweight, high tensile 1.5 mm thick 'Rustec' steel. Adjust 2-Fit side expander system that offers up to 24mm expansion to the structural opening. Strongdor self adhesive neoprene teardrop seal provided as standard. Various frame depths and styles are available.

Acoustic Rating Upgrade

Up to 39dB rating.

Fire Rating Upgrade

Fire-rated up to E120 and UKCA | CE marked to BS EN 14351-1 and EN 16034 standards.

- AUTOMATIC AND MANUAL DEADLOCKING
- HIGH SECURITY MICO TINDALL HARDWARE
- SIDE AND OVER PANELS AVAILABLE

Available with Secured By Design police prevention standard


Secured by Design



Official Police Security Initiative


	Single Door	Double Door
Width	Up to 1360mm	Up to 2610mm
Height	Up to 2550mm	Up to 2550mm

Single-point and Multi-point Locking




Multi-Point

Mounted lock and is available with an external access device




Multi-Point

Surface mounted lockable handle-set




Single-Point

Aluminium push pad




Single-Point

Aluminium push plate



Single-Point

Stainless steel push bar



Single-Point

Stainless steel electro-mechanical locking device



Securidor®

SR2

The Securidor S2 security door range comprises of single and double security-rated steel door-sets that are specifically designed for use in locations that would benefit from enhanced protection. The typical application for this range includes leisure facilities, schools and universities, housing association communal areas and general retail outlets.

These door-sets can only be supplied with outward opening leaves.

Leaf

44mm door leaf thickness, fitted with an integrated astragal for added security. The leaf skins are mechanically interlocked and internally bonded, providing greater stability and protection against de-lamination

Frame

Adjust 2-Fit side expander system that offers up to 24mm expansion to the structural opening.

Threshold

Industrial door threshold - 96mm Standard aluminium threshold is Part M compliant and is fitted with a seal for outward opening door-sets.

Fire Rating Upgrade

Fire-rated up to E120 and UKCA | CE marked to BS EN 14351-1 and EN 16034 standards.

Suitable Substrate

Structural timber, brickwork/ concrete blockwork. Steelwork also available on non fire rated doors.

	Single Door	Double Door
Width	Up to 1320mm	Up to 2200mm
Height	Up to 2700mm	Up to 2700mm



Securidor SR2

CERTIFIED BY THE LOSS PREVENTION CERTIFICATION BOARD TO LPS 1175 B3 ISSUE 8 CERT/LPCB AND LPS 1175 A5 ISSUE 8 CERT/LPCB

SUITABLE FOR INTERNAL AND EXTERNAL USE





Securidor+ SR3

The Securidor+ S3 security door range comprises of single and double security-rated steel door-sets that are specifically designed for use in locations that would benefit from enhanced protection. The typical application for this range includes retail outlets, cash rooms, warehouses and utility sub stations.

Leaf

Manufactured from 1.5mm galvanised attack face steel with 1.5mm inner face, the composite door leaf is 51mm thick with astragal lip to the closing edge.

Frame

The welded frame is made from reinforced 1.5mm galvanised steel and a 38mm x 100mm single rebated profile. It is reinforced at hinges, lock keeps and fixing points.

Hardware

Select from a range of high-quality hardware options including Hooply Cefiro multipoint lock, Mico Tindall AD1/AD2/AD3 push pad options, and Mico Tindall MD1/MD2/MD3 full push pad and lever handle hardware.

Certification by the Loss Prevention Certification Board to LPS 1175 SR3 Issue 7 Cert/ LPCB Ref. 1542a

	Single Door	Double Door
Width	Up to 1400mm	Up to 2510mm
Height	Up to 3060mm	Up to 3060mm



LPS1175: Issue 7
Certificate no: 931

Securidor+ SR4

The Securidor+ S4 security door range is accredited to offer a high level of security against potential attacks from heavy duty tools such as felling axes and disc grinders. The range is suited for use in high-security installations, such as the Ministry of Defence, banks, schools, utility buildings, sub-stations and Home Office approved gun rooms.

Leaf

Manufactured from 1.5mm steel on the inner and outer face, the composite door leaf is 45mm thick with an integral astragal lip to the closing edge.

Frame

The welded frame is made from reinforced 1.5mm steel and a 38mm x 100mm single rebated profile, reinforced at the hinges, lock keeps and fixing points.

Hardware

Choice of personnel, panic and escape hardware, with over 100 locking options available - including single and multi-point bolting. All escape hardware complies with BS EN 179.

Certification by the Loss Prevention Certification Board to LPS 1175 SR4 Issue 7 Cert/ LPCB Ref. 1542c

	Single Door	Double Door
Width	Up to 1284mm	Up to 2492mm
Height	Up to 2750mm	Up to 2750mm



LPS1175: Issue 7
Certificate no: 931