



Door pictured is inward opening

Attackdor[®]

LPS 1673

Steel Attack Door

SUITABLE FOR SECURITY
OF BUILDINGS

UNIQUE FEATURES

Fast Lead Times

NEW Security Certification

1 Year Warranty

Fast Quotes



LPS 1673 is a new security standard developed by the loss prevention certification board aimed to protect against violent forced entry attacks by individuals targeting people and valuable assets.

The typical applications for this range include locations at risk of targeted attacks against high profile individuals such as politicians, celebrities or high risk individuals.



Attackdor[®] LPS 1673 Issue 1 AR.A300 door-set specification

Leaf

44mm door leaf thickness, fitted with an integrated astragal for added security. Comprising of 2 x high strength 'Rustec' steel sheets, the leaf skins are mechanically interlocked and internally bonded, providing greater stability and protection against delamination.

Inward opening available only.

Frame

- Manufactured from lightweight, high tensile high strength thick 'Rustec' steel.
- Adjust 2-Fit side expander system that offers up to 24mm expansion to the structural opening.
- 50mm frame - perfectly complements installation to residential buildings where a slim low profile frame is required.

Also available with frame depths from 95mm - 300mm for single rebate and 140mm - 300mm double rebate.

70mm High-performance weather threshold

Available with AM3 inward opening threshold for excellent weather protection performance.

Certification

Certified by the Loss Prevention Certification Board to LPS 1673 Issue 1 AR.A300.

Certificate number: 1542e

Door ironmongery

- High security GU multipoint locking system with auto deadlock functionality.
- Electronic motorised deadlock retraction available as an access control upgrade - perfect for key-less entry smart control systems.
- Fixed knob or offset knob handle available to outside.
- Stainless lever handle on the inside allows free access to open the door from the secure side, but it can also be manually deadlocked, preventing the door from being opened from the inside.

Finish

Supplied inclusive of a powder coated finish from over 150 colours. Full range of RAL and BS colours available.

Available with a plain leaf style or traditional tongue and groove to enhance the appearance of the door and help it to blend into its surroundings as a residential style door-set.

Max door sizes

	Single Door
Width	Up to 1210mm
Height	Up to 2460mm